

**CENTRAL INSTITUTE FOR RESEARCH ON COTTON TECHNOLOGY
(INDIAN COUNCIL OF AGRICULARAL RESEARCH)
ADENWALA ROAD, MATUNGA , MUMBAI- 400019.**

Adm II/Pur/16/10-11

Dated : 11/08/2010

Sub : Desktop Computer

Sir.

Please send your lowest quotation with terms and conditions for supplying the following

Sr. No.	Specification	Require Quantity	Delivery Place
1.	<p>Technical Specifications: Processor : Intel® Core™ 2 Quad Processors with Intel vPro™ Technology Operating Systems : Genuine Windows Vista® Business Chipset : Intel® Q45 Express Chipset w/ICH10DO Memory : Four DIMM slots; Non-ECC dual channel 800MHz DDR2 SDRAM, supporting 1GB to 16GB with 4 GB installed RAM DVI Adapter card : Intel® Graphics Media Accelerator 4500 Hard Drives : 3.5" 7200RPM SATA II up to 320GB DVD Writer : DVD Writer with USB port Chassis - Mini-Tower - Number of Bays - 2 internal 3.5", 1 external 3.5", 2 external 5.25" Number of Bays Slots - Slot 1: 1 PCIe x16 full height graphics, Slot 2: 1 full height PCI, Slot 3: 1 full height PCI, Slot 4: 1 full height PCIe x1 Power Supply - 305W Standard Power Supply; 305W 88% Efficient Power Supply, ENERGY STAR 5.0 compliant, Active PFC Networking - Integrated Intel 10/100/1000 Ethernet Expandability - Standard I/O Ports: (1) VGA (12) USB 2.0 (4 front, 6 rear, 2 internal) MT (10) USB 2.0 (2 front, 6 rear, 2 internal) DT and SFF (1) 1 RJ-45 (2) PS2 (1) Display Port (1) Serial (1) parallel (1) ESATA (2) Line-in (stereo/microphone) (2) Line-out (headphone/speaker) Security - Setup/BIOS Password Display : Widescreen Flat Panel Monitor, Panel Size: 24 inches (24-inch wide viewable image size), Aspect Ratio: Widescreen (16:9), Panel Type: TN - Twisted Nematic, Optimal Resolution: 1600 x 900 at 60 Hz, Contrast Ratio: 1000 to 1 (typical), Brightness: 250 CD/m2 (typical), Response Time: 5ms panel typical, Viewing Angle: 160 vertical / 170 horizontal, Color Support: 16.7 million colors Pixel Pitch: 0.277 mm, Voltage Required: 100 to 240 VAC / 50 or 60 Hz + 3Hz / 1.6A (Max.) Printer: Colour : Print speed black (normal, A4) Upto 20 ppm, Print speed colour (normal, A4) Upto 15 ppm, Print quality black (best) Upto 600 x 600 dpi, Print quality colour (best) Upto 600 x 600 dpi, Print technology In-line colour laser printing technology Duty cycle (monthly, A4) Upto 50000 pages, Standard memory 64 MB, Maximum memory 320 MB, Processor speed 300 MHz, Paper handling Standard paper trays - 2, Maximum paper trays - 3, Paper handling standard/input 100-sheet multipurpose tray, 250-sheet input tray, Paper handling optional / input 500-sheet input tray, Paper handling standard/output 250-sheet top output bin, Duplex print options Manual (driver support provided), Media sizes supported A4, A5, B5 (JIS), executive (JIS), envelopes (DL, C5, B5), Media types supported Paper (bond, colour, letterhead, plain, preprinted, prepunched, recycled, rough), envelopes, labels, transparencies, Finished output handling Sheet fed Connectivity, Standard connectivity Hi-Speed USB 2.0 port, Fast Ethernet 10/100 Base -TX port Optional connectivity External HP Jetdirect print servers, Power and operating requirements Compatible operating systems Microsoft® Windows® 2000, XP Home, XP Professional, XP Professional x64, Server 2003; Windows Vista® Mac OS X v 10.2.8; Mac OS X v 10.3; Mac OS X v 10.4 or higher, Power requirements Input voltage 110 to 127 VAC (+/- 10%), 50/60 Hz (+/- 2 Hz); 220 to 240 VAC (+/- 10%), 50/60 Hz (+/- 2 Hz), Warranty: 1 Year Warranty (Return to Dealer - Standard Bench Repair) Printer: Black : Print speed black (normal, A4) Up to 26 ppm, Print quality black (best) Up to 1200 x 1200 dpi, Print technology, Monochrome Laser, Recommended monthly page volume 750 to 3000, Standard memory 32 MB, Maximum memory 288 MB, Processor speed 400 MHz, Paper handling standard/input : 250-sheet input tray, 50-sheet multi-purpose tray, Paper handling standard / output 125-sheet output bin, Duplex print options: Automatic (standard), Media sizes supported A4, A5, A6, B5, B6, C5, DL Media types supported Paper (bond, light, heavy, plain, recycled, rough), envelopes, labels, cardstock, transparencies, heavy media, Finished output handling: Automatic duplexing, manual feed, sheetfed, straight-through paper path Connectivity, Standard connectivity: Hi-Speed USB 2.0 compatible port, Power and operating requirements</p>	03	QEID, CIRCOT
		03	
		02	

	Compatible operating systems Microsoft® Windows® 2000, XP Home, XP Professional, Server 2003; Certified for Windows Vista™; Mac OS X v 10.2.8, Mac OS X v 10.3.9, Mac OS X v 10.4.3 or higher Power requirements Input voltage 110 to 127 VAC (+/- 10%), 60 Hz (+/- 2 Hz); 220 to 240 VAC (+/- 10%), 50 Hz (+/- 2 Hz) Warranty: 1 Year Warranty (Return to Dealer - Standard Bench Repair)		
--	--	--	--

Quotation should be in sealed cover super scribed "Quotation for **above mentioned in the sub. due on 25.08.10.** So reach this Institute on or before 25.08.10.

- ✓ The quotation without above superscription on the cover will not be considered.
- ✓ Validity of quotation should be indicated.
- ✓ Quotation received by fax will not be accepted.
- ✓ NET cost including all taxes should be clearly indicated.
- ✓ Quotation without indication of NET COST will be rejected.
- ✓ We do not issue any kind of concessional forms except excise duty.
- ✓ Delivery time and warranty period should be indicated.
- ✓ The party should quote the price for the above mentioned material. They should also quote separately the installation and testing charges.

Payment Conditions :

- 100 % of payment will be released 15 days after the delivery of ordered item good condition and subject to satisfactory report from the Indenting Officer..
- Time given delivery of Goods is 15 days after the receipt of Purchase Order.
- Penalty will be levied for delayed delivery.
- If the above payment conditions are agreeable, then only submit the Quotation.

Yours faithfully,

Head Of Office